

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 502700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35, T26-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4097-98)

A Fir 48" dia., for cor. of secs. 34 and 35, I mark T26S S35 on NE.; and R1W S34 on NW. side, with 2 notches on E. and 4 notches on W. side, from which
 A Hemlock 5" dia., bears N.31°E., 4 lks. dist. mkd. T26S R1W S35 BT.
 A Fir 40" dia., bears N.25°W., 15 lks. dist. mkd. T26S R1W S34 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 6, 1969 - C.S. File 54/94-31

Found - 48" D.Fir Corner tree, good scars.
 5" now 6" Hemlock N.31°E., 2.6 ft. scribe visible.
 40" now 46" D.Fir N.26°W., 9.9 ft. shows good scar.
Set Brass cap on N. side of Corner tree mkd:
 County Surveyors Office
 T26S R1W S 34 | S 35
 T27S 1969 S 2
New BT - 7" Hemlock N.75°E., 25.6 ft. mkd. T26S R1W S35 CS BT.
This corner lies 85.0 ft. W. of cor. to secs. 3 & 3, T27-1.