

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4814)

Set a basalt stone 15x10x5", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

 A fir, 30" dia., bears N.43°E., 37 lks., mkd: ¼ S23 BT.

 A cedar, 18" dia., bears S.40°W., 34 lks., mkd: ¼ S26 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Jan. 1970 - C.S. File 54/94-104

Found - No trace of a 15x10x5 cor, stone.

 30" D.Fir now 48" N.43°E. 24.4 ft. Shows a good axe face.

 14" Cedar now 30" S.40°W. 22.4 ft. Opened and found scribing of (4,2)

Set - Brass cap at ¼ the cor. mkd: COUNTY SURVEYORS OFFICE

T27S R1W

¼ S 23

S 26

1970

Rescribed BT- 30 Cedar S.40°W. 22.4 ft. Scribed ¼ S26 CS BT.

Note - This cor. lies 100 ft. E. approx., of a Cr. on a steep N. slope.