

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4816)

Set a basalt stone 15x15x8", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 14" dia., bears S.28°E., 64 lks., mkd: ¼ S23 BT.
A fir, 30" dia., bears N.12°W., 55 lks., mkd: ¼ S14 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-83

Found - 15x15x8 Corner Stone, in place, & mkd: "¼" on North face.
Orig. 30", now 50" D.Fir, N.12°W. 36.3 ft., shows good axe face.
Orig. 14" D.Fir, now 20" Stump, S.28°E. 42.2 ft., open & found scribe of ¼ S2 BT
Set - Brass Cap at ¼ Cor. at bearings & dist. and in place of cor. stone & mkd: COUNTY SURVEYORS T27S R1W
OFFICE ¼ S 14
1969 S 23
Rescrbd- 50" D.Fir N.12°W. 36.3 ft. mkd: ¼ S14 CS BT.
New BT - 6" Cedar S.45°E. 53.9 ft. mkd: ¼ S23 CS BT.
Note - This ¼ corner lies 70 ft. East about of ridge in a cutting unit.