TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4818)

Set a basalt stone 12x8x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 18" dia., bears N.68½°E., 46 lks., mkd: ¼ S11 BT.
A fir, 24" dia., bears S.17°W., 58 lks., mkd: ¼ S14 BT.

Douglas Co. Surveyors Office - Frank Jones - W. Penley - Nov. 1969 - C.S. File 54/94-51

Found - No Trace of Corner Stone nor SW BT.
18", now 30" D.Fir N.68½°E. 30.4 ft., opened & found scribing. We Rescribe: "¼ S11 CS BT".
Set - Brass Cap at Cor. mkd: County Surveyors Office 1969 T27S R1W ¼ S 11 / S 14
New BT - 40" D.Fir S.75°E. 14.7 ft. scribed "¼ S14 CS BT".
Note - This corner lies 75 ft. east of logging road.