

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4820)

Set a basalt stone 12x10x5", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A hemlock, 18" dia., bears S.25°W., 64 lks., mkd: ¼ S11 BT
A fir, 18" dia., bears N.15°W., 42 lks., mkd: ¼ S2 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94

Reported as not found.
This corner falls in rd or R/W near Emile(?) shelter. Found good E-W line.

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14573)

Point for the ¼ sec. cor. of secs. 2 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground with brass cap marked:

T27S R1W
¼ $\frac{S \ 2}{S \ 11}$
1971

from which
A fir, 50" dia., bears S.27¾°W., 58 lks., mkd: ¼ S11 BT.
A pine, 33" dia., bears N.66½°W., 43 lks., mkd: ¼ S2 BT.