

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 540640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Ronald Quimby & Romano Ware, BHW Eng. - For: US Forest Service - Aug. 1980 - M79-55

-----  
Set - 2½" IP with brass cap mkd: T27S R1W C¼ S2 RLS 1954 1980  
36" hemlock, N.14°W., 69.0 ft. "C¼ S2 BT"  
30" hemlock, S.30°E., 33.4 ft. "C¼ S2 BT"  
Brass washer marked RLS #1654 set in BT faces. Set post  
& sign 4.0 ft. north & 4.0 ft. east.  
Found - 3/4" iron rod, S.4°40'W., 20 ft. unrecorded.

Kristian DeGroot, LS #1941 BTS Engineering & Surveying - Crew: Les Fanning, Matt Dixon, & Aaron Fanning - Dec. 1997 - C.S. File 65/20-5

-----  
Found - 2½" iron pipe by Quimby & Ware in 1980 firmly set, projecting 5" above the ground with brass cap properly stamped.  
A 25" W.Fir, bears S.33°E., 23.2 ft. with scribe marks visible on a nearly healed double blaze. (Rec. Hemlock S.30°E., 33.4 ft.) 1980  
A 36° Hemlock, bears N.13°45'W., 68.8 ft. with scribe marks "C ¼ S2 BT" visible on a partially healed double blaze. (Rec. N.14°W. 69.0 ft)1980  
A 3/4"iron rod, bears S.4°40'W., 20.0 ft.  
Note - I paint BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.  
Magnetic Declination: 20°E.