

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4790-91)

Set a basalt stone 20x18x12 ins., 15" in ground for ¼ sec. cor. mkd. ¼ on N. face, from which
A Fir 26" dia., bears N.58°E., 28 lks. dist. mkd. ¼ S35 BT
A Fir 8" dia., bears S.34½°W., 16 lks. dist. mkd. ¼ S2 BT.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4094 and 4097)

(Page 4094)
The ¼ sec. cor. which is a basalt stone 6x12x12 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.
(Page 4097)
The old ¼ sec. cor. which I re-establish as the ¼ sec. cor. on N. bdy. of sec. 2, T27S R1W, only. I obliterate marks on N. face of stone and mark ¼ on S. face, from which
A Hemlock 8" dia., bears S.56°E., 62 lks. dist. mkd. ¼ S2 BT.
A Fir 8" dia., bears S.34°W., 16 lks. dist. mkd. ¼ S2 BT.
I obliterate marks on former bearing tree referring to sec. 35.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 3, 1969 - C.S. File 54/94-27

Found - Corner stone 20x18x15 mkd. "¼" on West face.
Unrecorded Alum. cap by corner stone mkd. US PC Prop Cor. T27S R1W S2 only T27S R1W RE 4287.
10" Hemlock S.56°E., 40.9 ft. remains of old stump.
New BTs- 22" Hemlock S.69°W., 72.0 ft. scribed ¼ S2 CS BT.
22" Hemlock S.26°W., 105.0 ft. scribed ¼ S2 CS BT.
This corner lies in West side of large cutting unit, 125 ft. E. of timber. 1/4 Cor. sec. 35 only, T26-1, lies East 70 ft.

BHW Engineering - Ronald Quimby; Romanso E. Ware - For: U.S. Forest Service - Aug. 1980 - M 79-55

Found - 1" I.P. with alum. cap mkd. "U.S.P.C. property corner T27S R1W 1963 1/4 S2 only RE 4287 Do Not Disturb".
20" Hemlock snag, S.69°W., 72.0 ft. visible scribe.
26" Hemlock S.26°W., 105.0 ft. visible scribes.
(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BT - 24" Hemlock S.61°W., 107.0 ft. "¼ S2 BT".
Brass washer mkd. RLS #1654 set in BT face. Set post & sign
4.0 ft. South.