

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs 25, 26, 35, 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4801)

-----

Set a basalt stone 15x10x8", 10" in the ground for cor. of secs. 25, 26, 35, & 36 mkd with 1 notch on S & E edges, from which

- A cedar, 18" dia., bears N.10°E., 38 lks., mkd: T27S R1W S25 BT.
- A hemlock, 20" dia., bears S.39½°E., 41 lks., mkd: T27S R1W S36 BT.
- A cedar, 10" dia., bears S.78°W., 28 lks., mkd: T27S R1W S35 BT.
- A fir, 16" dia. bears N.17°W., 55 lks mkd: T27S R1W S26 BT

Bruce Shaner - For: USFS 12/1965 - C.S. File 51/332

-----

Found - Basalt stone, from which

- 26" cedar, scribes visible, bears N.15°E., (rec. N.10°E.) 25.0 ft.
- 30" hemlock, scribes visible bears S.39½°E., 30.0 ft. (rec. 27.1 ft.)
- 14" cedar with old face, bears S.78°W., 18.5 ft.
- 16" fir, now stump with old face, bears N.12°W., (rec. N.17°W.) 36.3 ft.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-37

-----

Found - No trace of Corner Stone.

- 20", now 27" Hemlock S.39½°E. 32.6 ft. (Rec.27.1) scribe visible.
- 18" Cedar, now snag, N.10°E. 25.1 ft., shows scar.
- 10" now 12" Cedar, S.78°W. 18.5 ft., rotten face.
- 16" Fir, Now stump, N.17°W. 36.3 ft., stump rotted, old face, no scribing found.

Set - Brass Cap at Cor. mkd: COUNTY SURVEYORS T27S R1W  
OFFICE S 26 | S 25  
1969 S 35 | S 34

New BT - (no size given in notes)" D.Fir N.57°W. 31.3 ft.  
mkd: T27S R1W S26 CS BT.

Reblzd.& Resbd -  
12" Cedar S.78°W. 18.5 ft. mkd: T27S R1W S35 CS BT.  
No trees available to the N. E.