

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4805)

Set a basalt stone 20x12x10", 15" in the ground for 1/4 sec. cor. mkd. 1/4 on W face, from which
A cedar, 10" dia., bears N.25°E., 11 lks., mkd: 1/4 S24 BT.
A fir, 8" dia., bears N.36°W., 51 lks., mkd: 1/4 S23 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-95

Found - 8" hemlock stump (rec. Fir) N.36°W. 33.7 ft open for scribing "1/4". Ring count places face about 1902
10" cedar, now stump N.14°E., (rec. N.25°E.) 7.3 ft. found no face, probably logged.

Set - Using 2 dist. & 1 bearing I set brass cap at 1/4 cor mkd:
COUNTY SURVEYORS OFFICE
T27S R1W
1/4
S 23|S 24
1969

Note - This corner lies in clear cut unit. I set 3/4" iron rods in fir trail running north as follows, From the 1/4 cor.:
3/4" I.R. bears N.43°W., 24.4'
3/4" I.R. bears S.59°W., 21.3'
(North I.R. bears N.2°E., 29.0 ft. from South I.R.)
See sketch in file.

Ronald Quimby & Donald Bentz, BHW Eng. - For: USFS - Aug. 1980 - M79-56

Found - 1 1/2" I.P. with 1969 County brass cap properly marked.
24" Cedar stump N.14°E., 7.3 ft. vis. axe work.
19" Hemlock stump, N.36°W., 33.7 ft. vis. scribe.
3/4" iron rod, N.43°W., 24.4 ft.
3/4" iron rod, S.59°W., 21.3 ft.

New BTs- 10" Cedar, S.57°E., 52.2 ft. "1/4 S24 BT"
7" Hemlock, S.4°W., 45.4 ft. "1/4 S23 BT".

Brass washer marked RLS #1654 set in BT faces. Set post & sign 4 ft. South.