

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4805)

Set a basalt stone 15x12x8", 10" in the ground for cor. of secs. 13, 14, 23, & 24 mkd with 3 notches on S & 1 notch on E edges, from which

- A fir, 30" dia., bears NE., 27 lks., mkd: T27S R1W S13 BT.
(On scan of orig. line notes 45 is penciled in adjacent to the NE)
- A fir, 18" dia. bears S.28°E., 22 lks mkd: T27S R1W S24 BT
- A fir, 18" dia. bears S.40°W., 35 lks mkd: T27S R1W S23 BT
- A fir, 18" dia. bears N.57°W., 40 lks mkd: T27S R1W S14 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94-34

Found - 15x12x8" stone, firmly set mkd: 3 notches S & 1 East 30" D.Fir, now stump, N.45°E., 17.8 ft. show good scar.

- 18" D.Fir, now stump, S.28°E., 14.5 ft. shows good scar.
- 18" D.Fir, now snag, S.40°W., 23.1 ft. shows pitched over scribe.
- 18" now 30" D.Fir, N.57°W., 26.4 ft. shows good scar

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE S 14 | S 13
1969 S 23 | S 24

New BTs- 9" Hemlock N.18°E., 21.0 ft. mkd: T27S R1W S13 CS BT
8" Hemlock S.2°E., 40.3 ft. mkd: T27S R1W S24 CS BT
No other trees available.

Ronald Quimby & Duane Scroggins, BHW Eng. - For: USFS - Aug. 1980 - M79-57

Found - 1969 County brass cap on a 1½" I.P. properly marked.

- 34" D. Fir, N.57°W., 26.4 ft. Good scar.
- 12" Hemlock, N.18°E., 21.0 ft. vis. scribe.
- 10" Hemlock, S.2°E., 40.0 ft. vis. scribe.
- 30" Fir stump, N.45°E., 17.8 ft. Good scar.

New BT - 7" D.Fir, S.16°W., 27.2 ft. "T27S R1W BT"
Brass washer marked RLS 1654 set in BT face. Set post & sign 4 ft. South.

continued next page

1

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Kris DeGroot - For USFS - July 7, 2008 - C.S. File 65/63-37_

Found - A 1¼" iron post, firmly set, projecting 16" above the ground with a 2 Y2" diam. brass cap

From which bearing trees by Angell m 1902:

Orig. 18" now 31" D.Fir bears N.57°W., 26.4 ft. with a healed face (Rec. N.57°W., 40 lks).

Orig. 30" now 30" D.Fir stump bears N.48°E., 17.8 ft. I open pitch seam to reveal scribing "S 13" in old face (Rec. NE 27 lks).

Orig. 18" now a buckskin and rotting D. Fir snag bears S.28°E., 14.5 ft. with no visible scar or face (Rec. S.28°E., 22 lks).

Orig. 18" now 26" D.Fir snag bears S.40°W., 23.1 ft. with illegible scribing visible in previously opened face (Rec. S.40°W., 35 lks.).

And bearing trees by Powell in 1969:

Was 9" now 16" Hemlock snag bears N.18°E., 21.0 ft. with a healed face covered by 24" dia. fallen log

Was 8" now 11" Hemlock bears S.5½°E., 40.3 ft. with a healed face (Rec. S.2°E., 40.3 ft.).

And bearing tree by Quimby and Scroggins in 1980:

Was 7" now 13" D.Fir bears S.14½°W., 27.2 ft. with a healed double face (Rec. S.16°W., 27.2 ft.).

10" D. Fir bears S.64°E., 11.2 ft. with a healed double face (No record but appears to be same date and crew as M 79-57 in 1980).

New BT - A 9" Hemlock bears N.66°E., 32.6 ft. which I scribe "T27S R1W S13 BT" on double face.

All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All BTs have a 6" red band painted around the tree and the blazed face painted red and BT and USFS Land Survey Monument sign nailed to the tree.

Corner renewal date: July 30, 2008

Party Chief: Lester Fanning, PLS 2664

Witnesses: Scott McCurdy and Rick Sanford

Warren Knight Staff Compass -- decl. 18°E