

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4806)

Set a basalt stone 12x10x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which
 A fir, 24" dia., bears NE., 21 lks., mkd: ¼ S13 BT.
 (On scan of orig. line notes 45 is penciled in between the N and the E)
 A fir, 18" dia., bears S.69°W., 27 lks., mkd: ¼ S14 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Nov. 1969 - C.S. File 54/94

Reported as not found.
This cor. falls in old clear cut very brushy & badly burnt.

Ronald Quimby & Duane Scroggins, BHW Eng. - For: USFS - Aug. 1980 - M79-57

Found - Orig. stone with vis. ¼ on west side.
 Down 24" D.Fir N.45°E., 13.9 ft vis scribes "S13 BT"
Set - 2½" iron pipe with brass cap mkd: "T27S R1W ¼ S14 S13 RLS 1654 1980" Set cap at location of corner stone. Buried stone alongside.
New BTs- 8" D.Fir N.55°W., 3.9 ft. "¼ S14 BT"
 10" D.Fir N.36°E., 13.8 ft. "¼ S13 BT"
Brass washer marked RLS 1654 set in BT face. Set post & sign 2 ft. North.