

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4807)

Set basalt stone 18x10x8", 14" in the ground for cor. of secs. 11, 12, 13, & 14 mkd with 4 notches on S & 1 notch on E edges, from which

- A yew, 10" dia. bears N.73°E., 9 lks. mkd: T27S R1W S12 BT
- A fir, 34" dia. bears S.30°E., 44 lks mkd: T27S R1W S13 BT
- A hemlock, 18" dia., bears S.69°W., 10 lks., mkd: T27S R1W S14 BT.
- A hemlock, 18" dia., bears N.32½°W., 40 lks., mkd: T27S R1W S11 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-10

Found - No trace of corner stone.
10" now 11" yew, N.73°E., 5.9 ft. face rotted no scribed.
34" now 39" D.Fir S.30°E., 29.0 ft. shows good scar.
18" now 21" Hemlock S.69°W., 6.6 ft. scribe visible.
18" now 20" Hemlock N.26°W., (rec N.32½°W.) 26.4 ft. scribe visible.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE S 11 | S 12
1969 S 14 | S 13

New BTs- 30" D.Fir N.68°E., 21.8 ft. mkd: T27S R1W S12 CS BT

Ronald Quimby & Duane Scroggins, BHW Eng. - For: USFS - Aug. 1980 - M79-57

Found - 1969 county brass cap properly marked.
12" yew, N.73°E., 5.9 ft. good scar.
40" fir, S.30°E., 29.0 ft. good scar.
23" hemlock S.69°W., 6.6 ft. vis. scribes.
22" hemlock N.26°W., 26.4 ft. vis. scribes.
Down 30" D.Fir, N.68°E., 21.8 ft. good scar.

Rescribed - 12" Yew N.73°E., 5.9 ft. "T27S R1W S12 BT face"
Brass washer marked RLS 1654 set in BT face. Set post & sign 4 ft. South.