

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4808-9)

Set a basalt stone 15x8x6", 10" in the ground for cor. of secs. 1, 2, 11, & 12 mkd with 5 notches on S & 1 notch on E edges, from which

- A fir, 12" dia. bears N.18°E., 14 lks. mkd: T27S R1W S1 BT
- A fir, 14" dia. bears S.46°E., 39 lks mkd: T27S R1W S12 BT
- A fir, 14" dia. bears S.14°W., 37 lks mkd: T27S R1W S11 BT
- A fir, 12" dia. bears N.24°W., 42 lks. mkd: T27S R1W S2 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-14

Found - 15x8x6 stone firmly set at corner.
 12" now 26" D.Fir N.24°W., 27.7 ft., tree opened but not to face.
 12" now 30" W.Fir N.18°E., 9.2 ft., scribe visible through hole.
 14" now 35" W.Fir S.46°E., 25.7 ft. shows good scar.
 14" W.Fir, now stob, S.14°W., 24.4 ft scribe visible

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
 OFFICE S 2 | S 1
 1969 S 11 | S 12

New BT - 20" D.Fir S.40°W., 29.7 ft. mkd: T27S R1W S11 CS BT.
 All other BTs OK & tagged.

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14571)

The cor. of secs. 1, 2, 11, and 12, perpetuated by the Douglas County Surveyor, in 1969, with an iron pipe, 1½" dia., firmly set, protruding 14" above the ground, with brass cap (properly) mkd from which the original bearing trees

- A fir, 25" dia., bears N.18°E., 14 lks., with fragmentary scribe marks visible on partially healed blaze.
- A fir, 32" dia., bears S.46°E., 39 lks., with a healed blaze.
- A fir snag, 22" dia., bears S.14°W., 36 lks., with scribe marks T27S R1W S BT, visible on open blaze. (Record, 37 lks.)
- A fir, 25" dia., bears N.24°W., 42 lks., with partially opened blaze.

and bearing tree marked by the County Surveyor
 continued next page

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Cor Secs 1, 2, 11, & 12

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A fir, 22" dia., bears S.40°W., 44½ lks. mkd: T27S R1W S11
CS BT.
The original basalt cor, stone, 15x8x6" is set alongside the
iron pipe.