

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600633

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. Secs. 1 & 2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4810)

7 chains south of the point for ¼ sec. cor (falls in swamp) South side of swamp on line set a basalt stone 12x10x6", 8" in the ground for WC to ¼ sec. cor. mkd. WC ¼ on W face, from which

A hemlock, 14" dia., bears N.75°E., 3 lks. mkd: WC ¼ S1 BT
A hemlock, 20" dia., bears S.75°W. 23 lks. mkd: WC ¼ S2 BT

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14571-2)

The witness sec. cor. of secs. 1 and 2, determined from the remains of the original bearing trees:

A hemlock stump, 20" dia., bears N.75°E., 3 lks. with healed blaze, and buried under 3 ft. of road fill
A hemlock stump, 26" dia., bears S.75°W., 23 lks. with scribe marks WC¼ S2 BT visible on opened blaze.

At the original witness corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

T27S R1W
W C
¼
S 2 1S 1
1971

from which a new BT

A fir, 8" dia., bears N.87°W., 58 lks., mkd: X BT.

Ronald Quimby - Romano E. Ware, BHW Eng. - For: USFS - Aug. 1980 - M79-55

Found - 2½" I.P. with brass cap marked U.S. Dept. of the Interior T S R W WC S2 ¼ S1 1971".

10" D. Fir, N.87°W., 38.3 ft. vis. scribes.

24" Hemlock stump, S.77°W., 15.1 ft.

New BTs- 7" Fir, S.2°W., 8.9 ft "WC 1/4 S2 BT"

6" Fir, S.70°E., 12.0 ft. "WC 1/4 S1 BT"

Brass washer marked RLS #1654 set in BT faces. Set post & sign 4 ft. West.