

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4810)

-----  
The point for ¼ sec. cor. falls in swamp.

BLM dependent resurvey by Jasper M. Sams & Donovan C. Harris, Cadastral Surveyors, under Group No. 747, surveyed June/Aug. 1971 - (DCSO records Vol. 35 Page(s) 14572)

-----  
Point for ¼ sec. cor. of secs. 1 & 2, at proportionate dist. falls in a swamp where it is impracticable to established a permanent monument.

Ronald Quimby - Romanso E. Ware, BHW Eng. - For: USFS - Aug. 1980 - M79-55

-----  
Set - 2½" IP w/brass cap mkd: T27S R1W ¼ S2 S1 RLS 1654 1980  
36" W.Fir S.78°E., 103.6 ft. "¼ S1 BT"  
20" W.Fir S.83°W., 156.5 ft. "¼ S2 BT"  
Brass washers marked RLS #1005 set a BT faces. Set post & sign 3.0 ft. North & 3.0 ft. West.

Kristian DeGroot, LS #1941 BTS Engineering & Surveying - Crew: Les Fanning, Matt Dixon, & Aaron Fanning - Dec. 1997 - C.S. File 65/20-4

-----  
Found - 2½" iron pipe by Quimby & Ware in 1980 firmly set, projecting 3" above the ground with brass cap properly stamped.  
A 37" W.Fir with a snag top, bears S.80°45'E., 104.0 ft. with scribe mks: "¼ S1 BT" visible on a open blaze (Rec. S.78°E., 103.6 ft.) 1980  
A 28" W.Fir, bears S.81°45'W., 156.6 ft. with scribe marks visible on a open blaze. (Rec. S.83°W., 156.5 ft.) 1980  
New BT - A 22" W.Fir bears N.58°15'E., 70.7 ft. scribed "¼ S1 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed to the lower blaze.  
Note - I paint BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.  
Magnetic Declination: 20°E.