

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 602100

PRIMARY CORNER DESCRIPTION C C to secs. 1 & 2 only, T28-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 13 Page(s) 5381-82)

Set a basalt stone 15x12x10 ins., 10" in ground for closing cor. for secs. 1 and 2, marked C.C. on S. and with 1 notch on E. and 5 notches on W. edges; from which
A Fir 12" dia., bears S.18°E., 37 lks. dist., marked T28S R1W S1 BT.
A Fir 16" dia., bears S.61°W., 68 lks. dist. marked T28S R1W S2 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 15, 1969 - C.S. File 54/94

Found - 15x12x10 stone, firmly set, mkd. 1 notch E. side. 16" now 30" D.Fir S.61°W., 44.9 ft., shows good scar 12" D.Fir now stob, S.18°E., 24.4 ft. found scribing "S1 BT".

Set Brass cap at cor. mkd: County Surveyors Office
T27S R1W S 36
T28S CC S 2 | S 1
1969

New BT - 6" Cedar S.88°E., 15.2 ft. mkd. T27S R1W S1 CC CSBT
This corner lies 25 ft. E. of spring branch and 99.0 ft. E. of sec. cor. to 35 and 36, T27-1W.