

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by S.C. Flint, Contract #473, dated June 5, 1883  
-(DCSO records Vol. 11 Page(s) 4771)

-----  
Set post 44x4 ins., firmly in the ground for stan. ¼ sec.  
cor. marked S C on N. and S. faces, from which

A Fir 14" dia., bears N.70°W., 50 lks. dist. mkd. S C ¼ S  
BT.

A Fir 16" dia., bears S.45°W., 21 lks. dist. mkd. S C ¼ S  
BT.

GLO survey by Homer D. Angell, Deputy Surveyor, under  
Contract #746, dated May 5, 1902 - (DCSO records Vol. 11  
Page(s) 4772-73)

-----  
(39.27 chs.)

Old ¼ cor. on line which I destroy.

(40.00 chs.)

The point for ¼ sec. cor. falls on a flat rock in place 3 ft.  
by 3 ft. on which I cut a cross (X) at the exact cor. point  
for ¼ sec. cor. marked with S. C. ¼ on N. side, from which

A Fir 18" dia., bears N.50°E., 27 lks. dist. mkd. SC ¼ S36  
BT.

A Fir 18" dia., bears S.15°E., 10 lks. dist. mkd. SC ¼ S1  
BT.