TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4802)

Set a basalt stone 12x12x8", 8" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 14" dia., bears South, 24 lks., mkd: ¼ S36 BT.
A cedar, 10" dia., bears N.17½°W., 30 lks., mkd: ¼ S25 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Dec. 1969 - C.S. File 54/94-75

Found - 12x12x8 Stone, firmly set at ¼ corner, no marks fd.
14", now 24" Fir, North (rec. South) 15.8 ft., shows good scar.
10" now 12" Cedar, S.17°W. (Rec.N.17½°W.) 19.8 ft., scribe visible on rotten face.

Set - Brass Cap at Cor. mkd: County Surveyors Office 1969 ¼ S 25 / S 36

New BT - 16" D.Fir S.57½°W., 7.5 ft. mkd: "¼ S36 CS BT"