

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

... Mr. Powell, of DCSO, located many original corners in that era & in this township. Given the location of the stone, cut bank & his corner monument, Mr. Powell would of had to stand on or near the stone to set his monument if it had been in place. I agree with Mr. DeGroot and accept the 1969 corner monument. At the position determined by the base of the found iron pipe set a "deep1" magnet with washer and a 2½"x30" aluminum pipe with a ¾" aluminum cap flush in a 2.5 ft diameter mound of stone, invert & bury the DCSO monument alongside to the east & place the stone in the mound of stone west of the monument.

A 38" fir bears, S.16°57'E., 21.0 ft, with a healed single blaze. (S.15°E., 23.1 ft. 1902)
No trace found of a (10" fir)1902, falls in road cut. (N.41°W., 21.1 ft. 1902)
A 52" fir stump bears, S.89°54'E., 68.1 ft to spike set in top, healed blaze. (N.89°E., 68.8 ft 1969)
A 18" fir bears, N.6°27'E., 21.0 ft, with a healed double blaze. (N.7°E., 21.1 ft. 1980)

New - A magnetic spike marking the position of found stone bears S.55°E., 1.44 ft.
A 10" hemlock bears, S.49°31'W., 26.3 ft, marked "¼S24" "BT".
A 12" hemlock bears, N.12°05'W., 19.4 ft, marked "¼S13" "BT".

New BTs are marked on a double blaze & include a ¾" brass washer marked "ORPLS#89396" nailed flush in the lower blaze between the B & T

Note - Corner maintenance/other info: clear brush from around monument and to BTs. Tie flagging to monument and guard post, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.

LATITUDE: N 43°12'44.147" LONGITUDE: W 122°45'57.887"
Datum - WGS 84
Source- USGS Quad map for navigation to corner.