

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4807-8)

Set a basalt stone 12x12x6", 8" in the ground for 1/4 sec. cor. mkd. 1/4 on N face, from which
A fir, 30" dia., bears S.20°E., 17 lks., mkd: 1/4 S13 BT.
A hemlock, 20" dia., bears N.65°W., 65 lks., mkd: 1/4 S12 BT

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-11

Found - 12x12x6" stone mkd: 1/4 on north face.
30" now 26" D.Fir, S.20°E., 11.2 ft shows good scar.
20" hemlock now down N.65°W., 42.9 ft. scribe visible.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE S 12
1/4
1969 S 13

New BT - 7" hemlock N.15°E., 4.2 ft. scribed "1/4 S12 CS BT"