

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GL0 resurvey by Homer D. Angell, Deputy Surveyor, under contract #747, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4809)

Set a basalt stone 15x10x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 30" dia., bears South, 7 lks., mkd: ¼ S12 BT.
A fir, 30" dia., bears N.68°W., 57 lks., mkd: ¼ S1 BT.

Douglas Co. Surveyors Office - John Powell - Frank Jones & W. Penley - Oct. 1969 - C.S. File 54/94-13

Found - No trace of corner stone.
30" fir, now stump, south 4.6 ft. rotten face, scribe visible.
30" fir, now stump, N.68°W., 37.6 ft. shows good scar.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T27S R1W
OFFICE ¼ S 1
1969 S 12
New BTs- 7" D.Fir S.41°E., 19.7 ft. mkd: ¼ S12 CS BT
16" W.Fir N.45°E., 25.0 ft. mkd: ¼ S31 CS BT