

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 1 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4792)

-----  
Set a basalt stone 20x10x8 ins., 15" in ground for ¼ sec. cor. marked ¼ on N. face, from which  
A Fir 18" dia., bears S.20°W., 24 lks. dist. mkd. ¼ S1 BT.  
A Fir 18" dia., bears N.5°W., 25 lks. dist. mkd. ¼ S36 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4095 and 4096)

-----  
(Page 4095)  
The ¼ sec.cor. which is a basalt stone 6x10x8 ins., above ground, firmly set, marked and witnessed as described by the surveyor general.  
(page 4096)  
The old ¼ sec. cor. which I re-establish in its original position as the ¼ sec. cor. on N. bdy. of sec. 1, T27S R1W only, as follows:  
I obliterate marks on N. side of stone and mark ¼ on S. side, from which  
A Fir 16" dia., bears S.81°E., 34 lks. dist. mkd. ¼ S1 BT.  
A Fir 18" dia., bears S.20°W., 24 lks. dist. mkd. ¼ S1 BT.  
I obliterate marks on former bearing tree referring to sec. 36.

Douglas Co. Surveyors Office - John Powell - 10/27/69 - C.S. File 54/94

-----  
Not found.  
This cor. falls in road, all BTs taken by construction.