

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4793) and (dup. pg. 9832, Vol. 23)

-----  
Set a basalt stone 15x12x8 ins., 10" in ground for cor. of secs. 25, 30, 31 and 36, marked with 5 notches on N. and 1 on S. edges, from which  
A Hemlock 12" dia., bears N.11°E., 7 lks. dist. mkd. T27S R1E S30 BT.  
A Hemlock 8" dia., bears S.63°E., 25 lks. dist. mkd. T27S R1E S31 BT.  
A Hemlock 8" dia., bears S.45°W., 27 lks. dist. mkd. T27S R1W S36 BT.  
A Hemlock 12" dia., bears N.68°W., 20 lks. dist. mkd. T27S R1W S25 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9841-42)

-----  
Intersect the cor. of 24, 30, 31 and 36, which is a basalt stone, 12x8x7 ins. above ground, marked 5 notches on the N. and 1 notch on the S. edge.  
Alongside of old cor. stone:  
Set an Iron post 3 ft. long, 2" dia., 27" in the ground for the cor. of secs. 25 and 36 only, with brass cap marked:  
T27S | T27S  
S25 | S31  
S36 |  
R1W | R1E  
1927

from which  
A Hemlock 16" dia., bears N.11°E., 7 lks. dist. mkd. T27S R1E S30 BT. (Old BT)  
A Hemlock 12" dia., bears S.63°E., 25 lks. dit. mkd. T27S R1E S31 BT. (Old BT)  
A Hemlock 10" dia., bears S.45°W., 27 lks. dist. mkd. T27S R1W S36 BT. (Old BT)  
A Hemlock 14" dia., bears N.68°W., 20 lks. dist. mkd. T27S R1W S25 BT. (Old BT)  
I change this cor. to refer to secs. 25 and 36 only, destroying the old scribe marks on the NE. and SE. BTs.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 23, 1969 - C.S. File 54/94-98

-----  
Found - 10" Hemlock now 17", S.45°W., 17.8 ft., scribe visible "S". (Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

14" Hemlock now stub, N.68°W., 13.2 ft.  
Also found stone at sec. cor., no marks.  
Set Brass cap at cor. mkd: County Surveyors Office  
R T 27 S R  
1 S 25 | S 31 1  
W S 36 | E  
1969  
New BT - 7" Hemlock N.67½°W., 19.6 ft. scribed T27S R1W S25  
CS BT.