

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4795) and (Dup. Pg. 9833, Vol. 23)

-----  
Set a basalt stone 20x15x5 ins., 15" in ground for cor. of secs. 19, 24, 25 and 30, marked with 4 notches on N. and 2 notches on S. edges, from which  
A Fir 14" dia., bears N.82°E., 61 lks. dist. mkd. T27S R1E S19 BT.  
A Fir 10" dia., bears S.81°E., 60 lks. dist. mkd. T27S R1E S30 BT.  
A Fir 30" dia., bears S.20°W., 30 lks. dist. mkd. T27S R1W S25 BT.  
A Fir 30" dia., bears N.80°W., 10 lks. dist. mkd. T27S R1W S24 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9843-44)

-----  
Intersect the old cor. established for secs. 19, 24, 25 and 30, which is a basalt stone 6x10x12 ins. above ground, mkd. with 4 notches on the N. and 2 notches on the S. edges, I change this cor. to refer to secs. 24 and 25 only, obliterating the scribe marks on the NE. and SE. bearing trees.  
Alongside of old stone cor.;  
Set an iron post 3 ft. long, 2" in dia., 27" in the ground for the cor. of secs. 24 and 25 only, with brass cap marked:  
T27S T27S  
S24 S 30  
S25  
R1W R1E  
1927

from which  
A Fir 18" dia., bears N.82°E., 61 lks. dist. mkd. T27S R1E S19 BT. (Old BT)  
A Fir 10" dia., bears S.81°E., 61 lks. dist. mkd. T27S R1E S30 BT. (Old BT)  
A Fir 35" dia., bears S.25°W., 30 lks. dist. mkd. T27S R1W S25 BT. (Old BT)  
A Fir 34" dia., bears N.80°W., 10 lks. dist. mkd. T27S R1W S24 BT. (Old BT)