

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 700503

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only, T27-1E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9935)

At point of intersection (2.84 chs. N.1°00'E. of cor. of secs. 12 & 13) Set an Iron post, 3 ft. long, 2" dia., 14" in the ground to bedrock, supported in a mound of stone, with a 3 ft. base, 1 ft. high, for the closing cor. of secs. 7 & 18, with brass cap mkd.

	T27S	T27S	
	S 12	S 7	
		S 18	CC
	R1W	R1E	
	1927		

from which

A Fir 12" dia., bears N.64°E., 12 lks. dist. mkd. T27S R1E
S7 CC BT.

A Fir 16" dia., bears S.40°E., 40 lks. dist. mkd. T27S R1E
S18 CC BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 8, 1969 - C.S. File 54/94-79

Found - 1927 GLO brass cap, properly mkd., out of ground. 12" now 14" Fir, N.64°E., 7.9 ft., pitched over, scribing visible.

16" now 26" Fir, S.40°E., 26.1 ft., shows good scar.

All bearing trees OK and tagged.

RESET brass cap in mound of stone.