

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4798) and (Dup. Pgs. 9836-37, Vol. 23)

Set a basalt stone 15x10x6 ins., 10" in ground for ¼ sec. cor. marked with ¼ on W. face, from which
A Fir 18" dia., bears SE. 17 lks. dist. mkd. ¼ S7 BT.
A Fir 26" dia., bears S.68°W., 24 lks. dist. mkd. ¼ S12 BT.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9849)

Intersect the old ¼ sec. cor., established for secs. 7 and 12, which is a basalt stone 8x6x6 ins. above ground, marked ¼ on the W. face.

I change this cor. to refer to sec. 12 only, obliterating the old scribe marked of the SE. bearing tree.

Alongside of old stone cor.;

Set an Iron post 3 ft. long, 1" in dia., 27" in the ground, for the ¼ sec. cor. of sec. 12 only, with brass cap marked:
¼ S12
1927

from which

A Fir 22" dia., bears S.45°E., 17 lks. dist. mkd. ¼ S7 BT.
(Old BT)

A Fir 30" dia., bears S.68°W., 24 lks. dist. mkd. ¼ S12 BT. (Old BT)

A Fir 28" dia., bears N.69°W., 22 lks. dist. mkd. ¼ S12 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 12, 1969 - C.S. File 54/94

Found original stone and bearing trees. OK and tagged. No trace of 1927 GLO brass cap.