

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 700543

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only, T27-1E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9849)

-----  
Point for the ¼ sec. cor. of sec. 7 only.  
Set an Iron post 3 ft. long, 1" dia., 27" in the ground for the ¼ sec. cor. of sec. 7 only, with brass cap marked:

¼ S 7  
1927

from which

- A Fir 26" dia., bears N.45°E., 39 lks. dist. mkd. ¼ S7 BT
- A Fir 26" dia., bears S.62°E., 42 lks. dist. mkd. ¼ S7 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - Nov. 12, 1969 - C.S. File 54/94-38

-----  
Found - 1927 GLO brass cap, properly mkd.  
26" now 38" D.Fir S.62°E., 27.7 ft., shows good scar  
26" D.Fir now down, N.45°E., 25.7 ft. tree buried.  
New BT - 24" D.Fir S.22°E., 31.7 ft. mkd. ¼ S7 CS BT.