

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4799) and (Dup. Pg. 9838, Vol. 23)

Set a basalt stone 15x10x4 ins., 10" in ground for ¼ sec. cor. marked ¼ on W. face and raise a mound of stone, 2 ft. base, 1½ ft. high on the W. Pits impracticable. No trees in limits.

GLO resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9851)

Intersect the old ¼ sec. cor. established for secs. 1 & 6, which is a basalt stone 10x4x7 ins. above ground, marked ¼ on W. face.
This cor. will hereafter refer to sec. 1 only.
Alongside of old stone cor., Set an iron post 3 ft. long, 1" dia., 27" in the ground, for the ¼ sec. cor. of sec. 1 only with brass cap marked: ¼ S 1
1927
Raise a mound of stone, with a 3 ft. base, 2 ft. high W. of cor., as no bearing trees were available.

Douglas Co. Surveyors Office - John Powell - 10/30/69 - C.S. File 54/94

Not found.
Chained in this cor. from call at creek (1 ch.). No trace of cap. No BTs were used, mound of stone not found.