

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1; SE Cor. S 36, T26-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 11 Page(s) 4800) and (duplicate Pg. 9838, Vol. 23)

Set a basalt stone 20x18x12 ins., 15" in ground for cor. of Tps. 26 and 27 S., Rs. 1 E. and 1 W. marked with 6 notches on each side, from which

- A Fir 16" dia., bears N.83°E., 75 lks. dist. mkd. T26S R1E S31 BT.
- A Fir 24" dia., bears S.21½°E., 27 lks. dist. mkd. T27S R1E S6 BT.
- A Fir 20" dia., bears S.55½°W., 55 lks. dist. mkd. T27S R1W S1 BT.
- A Fir 24" dia., bears N.61°W., 48 lks. dist. mkd. T26S R1W S36 BT.

GL0 resurvey by Otto L. Draper, U.S. Transitman, under Special Instructions, dated Dec. 24, 1920 - (DCSO records Vol. 23 Page(s) 9852-53)

Intersect the old Tp. cor., established for Tps. 26 and 27 S., Rs. 1 W. and 1 E., which is a basalt stone 18x12x10 ins. above ground, marked with 6 notches on the N., S., E. and W. edges. I change this cor. to refer to Tps. 26 and 27 S., R1W only, destroying the marks on the E. side of the stone cor., and obliterating the old scribe marks on the NE. and SE. bearing trees.

Alongside of old cor. stone:

Set an iron post 3 ft. long, 3" in dia., 27" in the ground for the cor. with brass cap marked:

T26S		
R1W		T27S
S36		S 6
S 1		
T27S		R1E
1927		

from which

- A Fir 20" dia., bears N.83°E., 75 lks. dist. mkd. T26S R1E S1 BT (Old BT)
- A Fir 28" dia., bears S.21½°E., 27 lks. dist. mkd. T27S R1E S6 BT. (Old BT)
- A Fir 24" dia., bears S.55½°W., 55 lks. dist. mkd. T27S R1W S1 BT (Old BT)
- A Fir 28" dia., bears N.61°W., 48 lks. dist. mkd. T26S R1W S36 BT (Old BT)

(Cont. Next Page)

TOWNSHIP 27 RANGE 01 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1; & SE cor. S. 36, T26-1W

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - John M. Powell, and crew -
Oct. 29, 1969 - C.S. File 54/94-23

Found - 24" D.Fir, now stump, N.61°W., 31.7 ft. Tree open,
scribe visible.

20" D.Fir, now stump, S.55½°W., 36.3 ft., burnt
face.

Found no trace of 1927 GLO brass cap.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 26 S	R
1	S 36	1
W	S 1	S 6
	T 27 S	E
	1969	

New Bearing Objects:

3/4" Iron Rod, N.47°W., 28.1 ft.

3/4" Iron rod, S.80°W., 23.1 ft.