

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Cor Secs 29, 30, 31, & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper,  
US Transitman, under Special Instructions dated Dec. 24,  
1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23  
Page(s) 10022-3)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for  
cor. of secs. 29, 30, 31, & 32, with brass cap mkd

T27S R2E  
S 30 | S 29  
S 31 | S 32  
1929

from which

- A fir, 14" dia., bears N.13½°E., 42 lks., mkd: T27S R2E  
S29 BT.
- A fir, 22" dia., bears S.23¼°E., 56 lks., mkd: T27S R2E  
S32 BT.
- A fir, 24" dia., bears S.9½°W., 38 lks., mkd: T27S R2E S31  
BT.
- A fir, 8" dia., bears N.89°W., 109 lks., mkd: T27S R2E S30  
BT.