

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 10027)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 19, 20, 29, & 30, with brass cap mkd

T27S	R2E
S 19	S 20
S 30	S 29
1929	

from which

- A fir, 9" dia., bears N.20°E., 49 lks., mkd: T27S R2E S20 BT.
- A fir, 28" dia., bears S.22°E., 69 lks., mkd: T27S R2E S29 BT.
- A fir, 32" dia., bears S.49°W., 92 lks., mkd: T27S R2E S30 BT.
- A cedar, 36" dia., bears N.26°W., 108 lks., mkd: T27S R2E S19 BT.