

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION W C Secs. 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 24 Page(s) 10039)

N.0°04'W. bet. secs. 7 & 8
79.57 chs.
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for witness cor. of secs. 5, 6, 7, & 8, with brass cap mkd

W C
T27SR2E
S 6 | S 5
S 7 | S 8
1929

from which
A fir, 16" dia., bears N.83°E., 36 lks., mkd: W C T27S R2E S8 BT.
A fir, 18" dia., bears S.62°E., 68 lks., mkd: W C T27S R2E S8 BT.
A fir, 18" dia., bears S.61°W., 39 lks., mkd: W C T27S R2E S7 BT.
A fir, 26" dia., bears N.15°W., 31 lks., mkd: W C T27S R2E S7 BT.

80.00 chs
Point for cor. falls on unsafe ground on the S side of Twin Lakes Creek, where it is impracticable to establish a permanent cor.