

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 10010)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 20, 21, 28, & 29, with brass cap mkd

T27S R2E  
S 20 | S 21  
S 29 | S 28  
1929

from which

- A fir, 12" dia., bears N.66°E., 50 lks., mkd: T27S R2E S21 BT.
- A chinquapin, 12" dia., bears S.60°E., 20 lks., mkd: T27S R2E S28 BT.
- A pine, 16" dia., bears S.55°W., 75 lks., mkd: T27S R2E S29 BT.
- A fir, 12" dia., bears N.43½°W., 74 lks., mkd: T27S R2E S20 BT.