

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 10013)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 16, 17, 20, & 21, with brass cap mkd

T27S R2E  
S 17 | S 16  
S 20 | S 21  
1929

from which

- A fir, 12" dia., bears N.84°E., 48 lks., mkd: T27S R2E S16 BT.
- A fir, 26" dia., bears S.16°E., 97 lks., mkd: T27S R2E S21 BT.
- A fir, 24" dia., bears S.14°W., 60 lks., mkd: T27S R2E S20 BT.
- A fir, 10" dia., bears N.78½°W., 38 lks., mkd: T27S R2E S17 BT.