

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 10016)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 8, 9, 16, & 17, with brass cap mkd

T27S R2E  
S 8 | S 9  
S 17 | S 16  
1929

from which

- A hemlock, 38" dia., bears N.69°E., 65 lks., mkd: T27S R2E S9 BT.
- A fir, 24" dia., bears S.24°E., 45 lks., mkd: T27S R2E S16 BT.
- A fir, 20" dia., bears S.29°W., 39 lks., mkd: T27S R2E S17 BT.
- A fir, 34" dia., bears N.35°W., 13 lks., mkd: T27S R2E S8 BT.