

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 10001)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 9, 10, 15, & 16, with brass cap mkd

T27S R2E  
S 9 | S 10  
S 16 | S 15  
1929

from which

- A fir, 18" dia., bears N.29°E., 57 lks., mkd: T27S R2E S10 BT.
- A fir, 8" dia., bears S.31°E., 39 lks., mkd: T27S R2E S15 BT.
- A fir, 8" dia., bears S.43°W., 22 lks., mkd: T27S R2E S16 BT.
- A fir, 8" dia., bears N.65°W., 7 lks., mkd: T27S R2E S9 BT.