

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 9982)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 22, 23, 26, & 27, with brass cap mkd

T27S R2E  
S 22 | S 23  
S 27 | S 26  
1929

from which

- A pine, 48" dia., bears N.35°E., 115 lks., mkd: T27S R2E S23 BT.
- A cedar, 30" dia., bears S.61°E., 120 lks., mkd: T27S R2E S26 BT.
- A fir, 24" dia., bears S.71°W., 180 lks., mkd: T27S R2E S27 BT.
- A fir, 36" dia., bears N.75°W., 22 lks., mkd: T27S R2E S22 BT.