

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 9987)

-----  
Set an iron post, 3 ft. long, 2" dia., 20" in the ground to bed rock, supported by mound of stone, 2½ ft. base, 14" high, for cor. of secs. 10, 11, 14, & 15, with brass cap mkd

T27S R2E  
S 10 | S 11  
S 15 | S 14  
1929

from which

- A fir, 40" dia., bears N.4°E., 125 lks., mkd: T27S R2E S11 BT.
- A hemlock, 20" dia., bears S.55°E., 26 lks., mkd: T27S R2E S14 BT.
- A hemlock, 10" dia., bears S.43°W., 25 lks., mkd: T27S R2E S15 BT.
- A pine, 54" dia., bears N.12°W., 191 lks., mkd: T27S R2E S10 BT.