

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 533100

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 2 only, WC T28-2E

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10460

From) the standard ¼ cor. of sec. 35, on the S bdy. of T27S R2E and run

West, along S. bdy. of sec. 35.

7.03 (chs)

Set a basalt stone, 22x16x8", 16" in the ground, for witness cor. to ¼ sec. cor. of sec. 2 only, marked WC ¼ S2 on S face, from which

 A fir, 30" dia., bears S.1°E., 44 lks., mkd: WC¼ S2 BT.

 A fir, 30" dia., bears S.14°W., 130 lks., mkd: WC¼ S2 BT.

Raise a mound of stone, 2 ft. base, 1½ ft. high E of cor.

7.26 (chs)

True point for cor. falls on exposed surface rock.