

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 9967)

Set an iron post, 3 ft. long, 2" dia., 6" in the ground, to bedrock, supported in a mound of stone, 5 ft. base, 2 ft. high, for cor. of secs. 23, 24, 25, & 26, with brass cap mkd

T27S R2E
S 23 | S 24
S 26 | S 25
1929

from which

- A fir, 24" dia., bears N.18°E., 91 lks., mkd: T27S R2E S24 BT.
- A cedar, 10" dia., bears S.37½°E., 56 lks., mkd: T27S R2E S25 BT.
- A cedar, 10" dia., bears S.28°W., 48 lks., mkd: T27S R2E S26 BT.
- A fir, 16" dia., bears N.47°W., 106 lks., mkd: T27S R2E S23 BT.