

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 9969-70)

-----  
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 13, 14, 23, & 24, with brass cap mkd

T27S R2E  
S 14 | S 13  
S 23 | S 24  
1929

from which

- A fir, 30" dia., bears N.62°E., 72 lks., mkd: T27S R2E S13 BT.
- A hemlock, 8" dia., bears S.11°E., 66 lks., mkd: T27S R2E S24 BT.
- A fir, 40" dia., bears S.39°W., 30 lks., mkd: T27S R2E S23 BT.
- A fir, 34" dia., bears N.70°W., 87 lks., mkd: T27S R2E S14 BT.