

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION W C Secs 1, 2, 11, & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Norman D. Price, US Surveyor & Otto L. Draper, US Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Oct. 1928 - Aug. 1929 - (DCSO records Vol. 23 Page(s) 9975 & 9977-8)

-----  
Point for cor. of secs. 1, 2, 11, & 12 falls on precipitous slope, where it is impracticable to establish a permanent corner.

S.0°04'W., bet. secs. 1 & 2  
80.06 chs.

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for WC to cor. of secs. 1, 2, 11, & 12, with brass cap mkd:

T27S	R2E
S 2	S 1
S 11	S 12
W C	
1929	

from which

A fir, 10" dia., bears N.69°E., 84 lks., mkd: W C T27S R2E S1 BT.

A hemlock, 14" dia., bears S.51°E., 57 lks., mkd: W C T27S R2E S1 BT.

A fir, 48" dia., bears S.52°W., 67 lks., mkd: W C T27S R2E S2 BT.

A hemlock, 10" dia., bears N.12°W., 68 lks., mkd: W C T27S R2E S2 BT.