

TOWNSHIP 27 RANGE 02E POINT IDENTIFIER # 673100

PRIMARY CORNER DESCRIPTION CC Tsp Cor (WC) T28-2E & T28-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Lincoln Wilkes, USCE, under Group No. 62, Special Instructions dated Dec. 21, 1920, surveyed Sept 1926/Aug. 1927 - (DCSO records Vol. 24 Page(s) 10384-5

Intersect the Sixth Standard Parallel South, 7.35 ch. West from the cor. of Tps. 27S., Rs. 2 & 3 E.

Point of intersection falls on sloping bedrock.

Therefore at a point of 0.24 chs. W of true cor. point

Set an iron post, 3 ft. long, 3" dia., 27" in the ground for witness cor. to closing cor. of Tps. 28S., Rs. 2 & 3 E., with brass cap mkd:

T27S		R2E
S		36 WC
S 1		S 6
T28S		
C C		
1927		

from which

A fir, 24" dia., bears S.54°E., 88 lks., mkd: WC T28S R3E
S6 CC BT.

A fir, 24" dia., bears S.10°W., 16 lks., mkd: WC T28S R2E
S1 CC BT.