

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION CC for Secs. 30 & 31 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4931)

At point of intersection (200 lks. S.0°16'W. of the cor. of secs. 25 and 36), Set a Hemlock post 3 ft. long, 4" sq., 24" in the ground for closing cor. of secs.30 and 31 mkd. CC T27S R2W on E.; S31 on S.; and S30 on North with 1 groove on South and 5 grooves on North face, from which

A Fir 36" dia., bears N.50°E., 28 lks. dist. mkd. T27S R2W S30 BT.

A Fir 36" dia., bears S.75°E., 29 lks. dist. mkd. T27S R2W S31 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm Stoffel, crew - Aug/Sept 1962 - C.S. 49/28-10

Found - 30" Fir stump S.75°E., 19.1 ft., good scribing visible on old face.

36" Fir stump, uprooted, N.50°E., 18.5 ft. scribing visible.

Set Brass cap at cor. mkd: County Surveyors Office
T27S R2W C.S.

| S 30
| S 31
1962

A 1½" Iron pipe bears N.80°E., 1.1 ft.

Scribed- 36" Fir stump S.18°E., 59.4 ft. mkd. T27S R2W S31 CS BT.

In clear cut area. No trees available. Corner lies approx. 50 ft. North of timber access road.

Survey by Ronald Geisler - For: Champion International Co. - June/Aug. 1985 - M 90-71

Found - 1962 DCSO brass cap on an iron post, and the following accessories:

Uprooted Fir stump bears N.50°E., 18.5 ft. (Orig.)

30" Fir stump bears S.75°E., 19.1 ft. scribe marks visible. (Orig.)

34" Fir stump bears S.18°E., 59.4 ft. scribing visible (1962)

Also found a 1½" Iron pipe N.80°W., 1.2 ft. from cap. (1962 record, N.80°E., 1.2 ft.)

This corner is now an amended closing corner. See following Geisler corner)

(Cont. Next Page)

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31, (West)

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Set a 2½" alum. cap on a 2½" x 30" alum. flared pipe mkd. PLS 1988. (An amended closing cor. bears S.88°24'45"E., 17.29 ft.)

BTs- 13" Fir bears N.62°E., 6.15 ft. scribed T27S R2W S30 CC BT.

6" Hemlock bears S.07°E., 19.7 ft. scribed T27S R2W S31 CC BT.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22032-33)

The closing corner of secs. 30 and 31, T27S R2W., established by Geisler, in 1985, and is accepted as the cor., monumented with an aluminum post, 2" dia., firmly set, projecting 3" above the ground, with aluminum cap (properly) mkd.

from which the remains of bearing trees mkd. by Geisler

A fir, 19" dia., bears N.63½°E., 6.2 ft., with a healed blaze.

A roothole bears S.12½°E., 19.3 ft., with hemlock trunk, 9" dia., lying alongside, with illegible scribe marks visible on a partially healed blaze.

and a new bearing tree

A fir, 19" dia., bears S.32¾°E., 30.8 ft., mkd. T27S R2W S31 CC BT.

From this corner, the original closing cor. of secs. 30 and 31, T. 27 S., R. 2 W., remonumented by the Douglas County Surveyors Office in 1962, amended by Ronald G. Geisler, Oregon Professional Land Surveyor No. 1988, in 1985, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T27S R03W bears S.88°04'19"E., 17.57 ft., monumented with an iron post, 1½" dia., firmly set, projecting 8"., above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A roothole bears N.50°E., 18.5 ft., with fir trunk, 36" dia., lying alongside, no marks visible.

A sawed fir stump, 31" dia., bears S.75°E., 19.1 ft., no marks visible

and the remains of bearing trees mkd. by person(s) unknown

A fir, 12" dia., bears N.66½°E., 20.1 ft., with a healed double blaze.

A fir, 14" dia., bears S.23°E., 26.9 ft., with a healed double blaze.

A fir snag, 6" dia., bears S.63¾°W., 21.0 ft., with a healed double blaze.