

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only, T27-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4861) and (Dup. Pg. 4984)

Set Cedar post 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 36, 25, 31 and 30, marked T27S R2W S30 on NE.; R3W S25 on NW.; S36 on SW.; and S31 on SE. faces, marked with 5 notches on N. and 1 on S. edges, from which

A Fir 8" dia., bears N.50°E., 24 lks. dist. mkd. T27S R2W S30 BT.

A Cedar 24" dia., bears N.48°W., 52 lks. dist. mkd. T27S R3W S25 BT.

A Cedar 8" dia., bears S.30°W., 27 lks. dist. mkd. T27S R3W S36 BT.

A Fir 24" dia., bears S.68°E., 29 lks. dist. mkd. T27S R2W S31 BT.

GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4911)

The cor. of secs. 25, 30, 31 and 36 which is a post, firmly set, marked and witnessed as described by the Surveyor general, and which I now change to refer to secs. 25 and 36 T27S R3W only.

Survey by Ronald Geisler - For: Champion International Co. June/Aug. 1985 - M 90-71

Set a 2½" aluminum cap on a 2½" x 30" alum. flared pipe, mkd. PLS 1988, from which

14" Fir bears S.11°W., 11.0 ft. scribed T27S R3W S36 BT.

7" Fir bears N.45°W., 18.9 ft. scribed T27S R3W S25 BT.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22031-2)

The cor. of secs. 25 & 36 only, on the E. bdy. of the Tp., reestablished by proportionate measurement by Geisler, in 1985, and is accepted as the cor., monumented with an aluminum post, 2½" dia., firmly set, projecting 5" above the ground, with an aluminum cap (properly) mkd.

from which bearing trees mkd. by Geisler

A fir, 20" dia., bears S.13¾°W., 10.9 ft., with healed double blazes.

A fir, 12" dia., bears N.44¼°W., 18.8 ft., with healed double blazes.

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 100202

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only, T27-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The geographic position (NAD 1983 (CORS 2000)) of the corner of sections 25 and 36 only, on the east boundary of the township, was determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System, noted above, is as follows:

Latitude: 43°11'03.80"N. Longitude: 122°59'29.85"W.