

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Ronald G. Geisler - For: Champion International Co.
June/Aug. 1985 - M 90-71

Set a 2½" aluminum cap on a 2½ x 30" alum., flared pipe mkd.
PLS 1988, from which
7" Fir bears S.87°E., 45.6 ft.
7" Cedar bears N.42°E., 21.9 ft.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore,
Cadastral Surveyors & Robert H Browning, Survey Technician,
under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO
records Vol. 56 Page(s) 22033-4)

The ¼ sec. cor. of sec. 30 only, T27S R2W established by
Geisler, in 1985, and is accepted as the cor., monumented
with an aluminum post, 2½" dia., firmly set, projecting 12"
above a collar of stone, 1½ ft. base, 1 ft. high, with
aluminum cap (properly) mkd.
from which bearing trees mkd. by Geisler
A cedar, 13" dia., bears N.43°E., 21.8 ft., with a healed
double blaze.
A fir, 15" dia., bears S.86°E., 45.5 ft., with a healed
double blaze.