

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 25 only, T27-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by S.C. Flint, Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4861) and (Dup. Pg. 4984)</p> <p>-----</p> <p>Set Cedar post 3 ft. long, 4" sq., firmly in the ground for ¼ sec. cor. marked ¼ S on E. and W. faces, from which</p> <p> A Hemlock 10" dia., bears N.82°E., 13 lks. dist. mkd. ¼ S BT.</p> <p> A Fir 40" dia., bears S.65°W., 48 lks. dist. mkd. ¼ S BT.</p>
<p>GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4911)</p> <p>-----</p> <p>The ¼ sec. cor. which is a post firmly set, marked and witnessed as described by the Surveyor General and which I now change to refer to secs. 25, T27S R3W only.</p>
<p>Survey by Ronald G. Geisler - For: Champion International Co. June/Aug. 1985 - M 90-71</p> <p>-----</p> <p>Set a 2½" aluminum cap on a 2½" x 30" alum., flared pipe mkd. PLS 1988., from which</p> <p> 2" Hemlock bears N.88°W., 11.1 ft. scribed X BT.</p> <p> 3" Fir bears S.18°W., 19.2 ft. scribed X BT.</p>
<p>BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore, Cadastral Surveyors & Robert H Browning, Survey Technician, under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO records Vol. 56 Page(s) 22034)</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 25 only, reestablished by proportionate measurement by Geisler, in 1985, and is accepted as the cor., monumented with an aluminum post, 2½" dia., firmly set, projecting 5" above the ground, with aluminum cap (properly) mkd.</p> <p>from which bearing trees mkd. by Geisler</p> <p> A fir, 9" dia., bears S.16½°W., 19.1 ft., with a healed double blaze.</p> <p> A hemlock, 5" dia., bears N.89¼°W., 10.9 ft., with a healed double blaze.</p>