

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 100344

PRIMARY CORNER DESCRIPTION E. 1/4 cor. Sec. 24 only, T27-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Contract #454, dated June 19, 1882
(DCSO records Vol. 12 Page(s) 4860) and (Dup. Pg. #4983)

set Cedar post 3 ft. long, 4" sq., for ¼ sec. cor. firmly in
the ground marked ¼ S on E. and W. faces, from which
A Hemlock 36" dia., bears N.82°E., 33 lks. dist. mkd. ¼ S
BT.
A Cedar 10" dia., bears N.20°W., 32 lks. dist. mkd. ¼ S BT

GLO Resurvey by Morris Wygant, Compassman for Zachariah
Derrick, U.S. Deputy Surveyor, Under Contract #779, dated
Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4912)

The ¼ sec. cor. which is a post firmly set, marked and
witnessed as described by the Surveyor general, and which I
now change to refer to sec. 24, T27S R3W only.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Dec. 1966 - C.S. File 54/40-3

Looked for, not found.
Found possible Cedar BT, scribe appears redone on burned
face. No Hemlock to NE. Find D.Fir, bark badly burned.

BLM dependent resurvey by A. Bert Skeesick & Timothy J Moore,
Cadastral Surveyors & Robert H Browning, Survey Technician,
under Group No. 1968, surveyed Aug. 2003/July 2004 - (DCSO
records Vol. 56 Page(s) 22038)

Point for the ¼ sec. cor. of sec. 24 only, determined by the
Broken Boundary Method. There is no remaining evidence of
the original cor.
Drive a finned aluminum rod, 72" long, ¾" dia., 68" in the
ground, with aluminum cap mkd.

T 27 S
R3W | R2W
¼ |
S 24 |
2003

from which
An alder, 8" dia., bears S.45¾°W., 8.7 ft., mkd. ¼ S24 BT
in the bark.
An alder, 6" dia., bears N.43¾°W., 5.7 ft., mkd. ¼ S24 BT
in the bark.
Deposit a magnet in a white plastic case alongside the finned
aluminum rod.
Corner is located in a wet marshy area.