

PRIMARY CORNER DESCRIPTION Tp Cor. T27-3 and T27-2 (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Samuel Flint, under Contract #459 dated Aug. 3, 1882 (DCSO records, Volume 10 Page 4180)

-----

A Fir post 4" sq. marked T27S R2W S6 on SE.; T27S R3W S1 on SW.; T26S R3W S36 on NW,; T26S R2W S31 on NE, faces with 6 notches on each edge of post N, S, E and W, from which

A Laurel 12" dia., bears S.5°E., 66 lks mkd T27S R2W S6 BT

A Fir 16" dia., bears S.38°W., 7 lks., mkd T27S R3W S1 BT

A Laurel 5" dia. bears N.25°W., 59 lks mkd T26S R3W S36 BT

No tree near in sec. 31.

BLM resurvey by Harold D. Corbin, Group No. 350 - Surveyed Aug 20, 1959/ Nov. 3, 1958 (DCSO Records, Volume 29 Pg 12442)

The cor. of Tps. 26 and 27 S., Rs. 2 and 3 W., determined at record bearing and distance from the only remaining original bearing tree:

A Fir 32" dia., bears S.38°W., 7 lks., with illegible scribe marks visible on a partially opened blaze.

and locally established bearing trees:

A rotted madrone, bears S.22°W., 37 lks., with illegible scribe marks visible on a partially opened blaze.

A madrone 10" dia., bears N.39°W., 68 lks. with illegible scribe marks visible on a partially opened blaze.

at the corner point  
Set an iron post, 28" long 2½" dia., 26" in the ground, with brass cap marked:

T	26	S
R	3	W
S	36	S
S	1	S
T	27	S
1958		

from which

A Fir 6" dia. bears N.51½°E., 27 lks. mkd T26S R2W S31 BT

A Fir 23" dia., bears S.46°E., 11 lks. mkd T27S R2W S6 BT

A Fir 18" dia., bears S.76°W., 25 lks. mkd T27S R3W S1 BT

A Fir 10" dia. bears N.24°W., 65 lks. mkd T26S R3W S36 BT

Found OK, DCSO, Gary Langlitz, Nov. 3, 1976, C.S. 59/26-6

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - Feb 2011 - M162-6

-----

Found - 1958 BLM Brass cap with the following accessories:

35"x4' D.Fir stump bears S.38°W., 4.6' - vis. scribing.

13" D.Fir stump bears N.51½°E. 17.8' - healed face.

continued next page

PRIMARY CORNER DESCRIPTION Tp Cor. T27-3 and T27-2 (North)


Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

28"x6' D.Fir stump bears S.46°E. 7.6' - healed face  
 15"x6' D.Fir stump bears S.76°W. 16.5'- healed face  
 13"x4' D.Fir stump bears N.24°W. 42.9'- healed face  
 New - 13" D.Fir bears S.86°W., 13.6' - blazed, scribed  
 "T27S R3W S1 BT"

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 229917-8)

-----  
 MEMORANDUM: The cor. of Tps. 26 and 27 S., Rgs. 2 and 3 W., was established by A. Flint in 1855 while surveying the S. bdy. of Tp. 26 S., R. 3 W. A position was also established by S. Flint in 1882, while surveying the E. bdy. of Tp. 27 S., R. 3 W. and given the same cor. designation. The cor. positions were erroneously reported as common in the resurveys performed by Collier and Corbin, but now function as the cors. of their respective townships.

The cor. of Tp. 27 S., Rgs. 2 and 3 W., formerly designated as the cor. of Tps. 26 and 27 S., Rgs. 2 and 3 W., established by S. Flint in 1882, perpetuated by Corbin in 1958, further perpetuated by Rice, in 2011, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap mkd.



from which the remaining original bearing tree  
 A sawed fir stump, 38" dia., bears S.38°W., 4.6 ft., with scribe marks T2 R visible on a partially opened blaze. and the remains of bearing trees mkd. by Corbin  
 A fir, 13" dia., bears N.51½°E., 17.8 ft., with a healed blaze.  
 A sawed fir stump, 28" dia., bears S.46°E., 7.3 ft., with a healed blaze.  
 A sawed, decayed fir stump, 6 ft. high, 18" dia., bears S.76°W., 16.5 ft., with a healed blaze.  
 A sawed, decayed fir stump, 14" dia., bears N.24°W., 42.9 ft., with a healed blaze.  
 and a bearing tree mkd. by Rice  
 A fir, 13" dia., bears S.84¾°W., 13.6 ft., with scribe marks T27S R2W S1 BT visible on an open blaze.  
 At the corner point

continued next page

TOWNSHIP 27 RANGE 02 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION  Tp Cor. T27-3 and T27-2 (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Change the cap markings to now read

T26S R2W  
S 31  
-----  
S 1 | S 6  
R3W R2W  
T27S  
2011  
1958

from which new bearing trees

A fir, 6" dia., bears S.8¼°E., 18.3 ft. mkd T27S R2W S6 BT

A fir, 10" dia., bears S.32°W., 14.0 ft mkd T27S R3W S1 BT

This cor. is now designated as the cor. of Tp. 27 S., Rgs. 2 and 3 W.

(The Tps corner for T26-2 & T26-3 (south) bears S.68°09'06"W. 41.24 ft)