

PRIMARY CORNER DESCRIPTION A P on So. bdy. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by S.C. Flint, Contract #459, dated August 3, 1882 - (DCSO records Vol. 12 Page(s) 4863)</p> <p>-----</p> <p>Set Cedar post 3 ft. long, 3" sq., 24" in the ground for standard ¼ sec. cor. marked on N. face S C ¼ S, from which  A Fir 18" dia., S.40°W., 29 lks. dist. mkd. SC ¼ S BT.  A Fir 24" dia., N.10°E., 18 lks. dist. mkd. S C ¼ S BT.</p>
<p>GLO Resurvey by Morris Wygant, Compassman for Zachariah Derrick, U.S. Deputy Surveyor, Under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 12 Page(s) 4907)</p> <p>-----</p> <p>The standard ¼ sec. cor. which is a post, firmly set, mkd. and witnessed as described by the surveyor general, bears S. 10 lks. dist. I now change this cor. to an Angle Point as follows:  Cut out all marks and remark A P on N. face, the cut out all bTs and remark A P BT.</p>
<p>Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Oct. 28, 1968 - C.S. File 54/40-99 (also C.S. 54/40-124)</p> <p>-----</p> <p>Found - 11" D.Fir S.65°E., 19.0 ft. mkd. AP S6 BT, alum. tag #4287.  11" D.Fir N.4°W., 33.3 ft. mkd. AP S31 BT, alum. tag #4287.  We find no original BTs. Above BTs unrecorded at this time.</p>
<p>Thomas A. Shrum, Jr. - For: U.S. Plywood - Dec. 1968 - M 37-17</p> <p>-----</p> <p>Set 2½" dia. alum. cap mkd. "A.P. T27S R2W S6 S31 T28S", from which  10" D.Fir S.65°E., 11.1 ft. "A.P. S6 BT RE 4287"  10" D.Fir N.02°W., 33.3 ft. "A.P. S31 BT RE 4287".</p>
<p>BHW Engineering, Ronal A. Quimby - For: U.S. Forest Service -March 1980 - M 79-37</p> <p>-----</p> <p>Found - 1" .P. with alum. cap mkd. U.S.P.C. prop. cor. T27S R2W AP S31 S6 T28S R2W RE 4287 1968".  12" Fir N.2°W., 33.3 ft.  12" Fir S.65°E., 11.1 ft.  New BTs- 14" Cedar S.14°W., 10.0 ft. mkd. "A.P. S6 BT"  6" Fir S.66°W., 34.5 ft. "A.P. S6 BT"  Brass washers in BT faces. Set fiberglass post and sign 2.0 ft. North.</p>